



# **D070KXM**

|                          |                                                  |                         |
|--------------------------|--------------------------------------------------|-------------------------|
| Operating Current        |                                                  | 10-20 mA (12-24V AC/DC) |
| Operational Frequency    |                                                  | 50 Hz                   |
| Operational Voltage      |                                                  | 12-30V AC/DC            |
| Product                  |                                                  | Pilot                   |
| Color                    |                                                  | Blue                    |
| Illumination             |                                                  | with LED                |
| Dia                      |                                                  | 16 mm                   |
| Head Type                |                                                  | Square                  |
| Power Consumption        |                                                  | 0.6 W                   |
| Insulation Voltage       | <b>Ui</b>                                        | 300V                    |
| Operating Temperature    |                                                  | -15 / + 70 °C           |
| Pollution Degree         |                                                  | 3                       |
| Protection Degree        |                                                  | IP50                    |
| Cable Section            |                                                  | Terminal 2,8x0,5        |
| Production Time          |                                                  | 31.12.1899 00:00:00     |
| Serial                   |                                                  | D Series Plastic        |
| Electrical Life          | <b>Min Hour</b>                                  | 10000                   |
| Specifications           | Non-flammable V0 PA6.6 contact blocks            |                         |
|                          | Various illumination contact blocks availability |                         |
|                          | Variety of products for all areas of application |                         |
|                          | Ease of use in limited spaces                    |                         |
| Standards / Certificates | TS EN 60947-5-1                                  |                         |

