



# EBM606PD14

|                                       |                            |                   |
|---------------------------------------|----------------------------|-------------------|
| Operating Current                     | 35A                        |                   |
| Product                               | Multipole                  |                   |
| Type                                  | Wall Type Socket           |                   |
| Contact                               | 6 Poles                    |                   |
| Usage Category                        | AC15                       |                   |
| Mechanical Life                       | Min Qty                    | ≥ 500             |
| Electrical Life                       | Min Qty                    | ≥ 100             |
| Operating Frequency                   | On-Off/Hour                | Mech.240 Elec.120 |
| Insulation Voltage                    | Ui                         | 690V              |
| Impulse Withstand Voltage             | Uimp                       | 6 kV              |
| Dielectric Strength (Body-Contact)    | 1890V AC                   |                   |
| Dielectric Strength (Contact-Contact) | 3000V AC                   |                   |
| Isolation Resistance                  | 10 MΩ Min. (500 V DC)      |                   |
| Operating Temperature                 | -40 / +125 °C              |                   |
| Pollution Degree                      | 3                          |                   |
| Protection Degree                     | IP65                       |                   |
| Body Material                         | Metal                      |                   |
| Production Time                       | 31.12.1899 00:00:00        |                   |
| Serial                                | EBM Series                 |                   |
| Entry                                 | Side Entry                 |                   |
| Locking                               | 4 Handle                   |                   |
| Specifications                        | Wide product variety       |                   |
|                                       | IP65 in closed position    |                   |
|                                       | Universal inserts          |                   |
|                                       | Easy cabling               |                   |
|                                       | Different locking types    |                   |
|                                       | Powdercoated metal housing |                   |
| Standards / Certificates              | TS EN 61984                |                   |

