



### EKS116PG1

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Operating Current                     | 16A                                      |
| Product                               | Kauçuk Fiş Priz                          |
| Type                                  | Wall Type Socket                         |
| Contact                               | 2P+E                                     |
| Usage Category                        | AC15                                     |
| Mechanical Life                       | Min Qty ≥ 5.000                          |
| Electrical Life                       | Min Qty ≥ 1.000                          |
| Operating Frequency                   | On-Off/Hour Mech.240 Elec.120            |
| Insulation Voltage                    | Ui 690V                                  |
| Impulse Withstand Voltage             | Uimp 2 kV                                |
| Dielectric Strength (Body-Contact)    | 1890V AC                                 |
| Dielectric Strength (Contact-Contact) | 2000V AC                                 |
| Isolation Resistance                  | 10 MΩ Min. (500 V DC)                    |
| Operating Temperature                 | -40 / +80 °C                             |
| Pollution Degree                      | 2                                        |
| Protection Degree                     | IP44                                     |
| Production Time                       | 31.12.1899 00:00:00                      |
| Serial                                | EKS Series                               |
| Specifications                        | Monoblock durable rubber plastic housing |
| Standards / Certificates              | TS IEC 60884-1-A1+A2                     |